## **CLAIMS**

## What is claimed is:

- 1 1. Folded film used to create a lap seal using an L sealer, comprising:
- a first film folded substantially in a form of a "J"; and
- a second film overlapping at least a portion of the first film,
- 4 wherein the first film and the second film are coupled together in at least a
- 5 portion of an overlapping area.
- 1 2. The folded film of claim 1, wherein the first film and second film are rolled
- 2 onto a tubular core to form a roll of film.
- 1 3. The folded film of claim 2 wherein the roll of film further comprises core
- 2 chucks on opposing sides of the tubular core.
- 1 4. The folded film of claim 2, wherein the roll of film has a diameter that is
- 2 smaller than a diameter of the core chucks.
- 1 5. The folded film of claim 1/2, wherein at least one of the first film or the
- 2 second film further comprises at least one perforation.
- 1 6. The folded film of claim 1, wherein the portion of the overlapping area
- 2 . comprises a plurality of perforations.
- 7. The folded film of claim 1, wherein the overlapping area further comprises
- 2 printing.

- 1 8. The folded film of claim 1, wherein the first and second films are made
- 2 from materials selected from the group comprising polyolefin,
- 3 polyvinylchloride, polyprøpylene, or any combination thereof.
- 1 9. A method of forming film used to create a lap seal, comprising the steps
- 2 of:
- 3 providing a first film;
- 4 applying a second film to overlap at least a portion of the first film; and
- 5 coupling the first film to the second film in at least a portion of an
- 6 overlapping area of said first and second films.
- 1 10. The method of claim 9, wherein the step of coupling further comprises
- 2 the step of creating at least one perforation in at least one of the first or
- 3 second films.
- 1 11. The method of claim 9, wherein the step of coupling comprises a step
- 2 selected among the steps in the group comprising coupling using a drag wire,
- 3 coupling using hot melt, or coupling using static points.
- 1 12. The method of claim 9 wherein the method further comprises the step
- 2 of substantially center folding the coupled first and second films to provided
- 3 folded film.
- 1 13. The method of claim 12, wherein the method further comprises rolling
- the folded film onto a tubular core to form a roll of folded film.
- 1 14. The method of claim 9 wherein the method further comprises the step
- 2 of printing onto the overlapping area.

{WP068788;1}

- 1 15. A method of shrink wrapping an item to form a lap seal using an "L"
- 2 sealer machine, comprising the steps of:
- dispensing pre-folded film having a pre-existing lap seal on the pre-
- 4 folded film onto a separator table of the L sealer machine;
- 5 inserting an item between the separator table and a first side of the pre-
- 6 folded film; and
- 7 sealing the item on at least two sides using a substantially L-shaped
- 8 heated bar forming a substantially wrapped item.
- 1 16. The method of claim 15, wherein the step of dispensing further
- 2 comprises the step of perforating the pre-folded film as the pre-folded film is
- 3 being dispensed.
- 1 17. The method of claim 15, wherein the pre-folded film is already pre-
- 2 perforated.
- 1 18. The method of claim 15, wherein the method further comprises the step
- 2 of heating the substantially wrapped item to force a substantial portion of air
- 3 between the pre-folded film and the item out of at least one perforation in the
- 4 pre-folded film.
- 1 19. A method of forming film used to create at least one lap seal,
- 2 comprising the steps of:
- 3 providing at least a first film;
- applying a subsequent film to overlap at least a portion of the first film;
- 5 and

- 6 coupling the first film to the subsequent film in at least a portion of an
- 7 overlapping area of said first and subsequent films.
- 1 20. The method of claim 19 wherein the method further comprises the step
- 2 of repetitively overlapping additional films to a previous film and repetitively
- 3 coupling such additional films to the previous film to form a roll of overlapping
- 4 film.
- 1 21. The method of claim 20, wherein the roll of overlapping film has a
- 2 plurality of film portions of substantially the same dimensions.